

## APC Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect

SMT2200RMI2UC



- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: Documentation CD, Rack mounting hardware, Rack Mounting support rails, USB cable

Output	
Output power capacity	1.98kWatts / 2.2kVA
Max Configurable Power (Watts)	1.98kWatts / 2.2kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup) (1) IEC 320 C19 (Battery Backup) (3) IEC Jumpers (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	British BS1363A, IEC-320 C20, Schuko CEE 7/EU1-16P
Cord Length	2meters
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V
Number of Power Cords	1

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect | SMT2200RMI2UC

Input	
Other Input Voltages	220, 240

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	<a href="#">RBC43</a> 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	169Watts
Battery Volt-Amp-Hour Capacity	509
Runtime	<a href="#">View Runtime Graph (Available in Technical Tab on site)</a> <a href="#">View Runtime Chart (Available in Technical Tab on site)</a>
Efficiency	<a href="#">View Efficiency Graph (Available in Technical Tab on site)</a>

Communications & Management	
Interface Port(s)	RJ-45 Serial, SmartSlot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	375Joules

Physical	
Maximum Height	86MM, 8.6CM
Maximum Width	432MM, 43.2CM
Maximum Depth	683MM, 68.3CM
Rack Height	2U
Net Weight	42.31KG
Shipping weight	49.73KG
Shipping Height	254MM, 25.4CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS 2200VA LCD RM 2U 230V with SmartConnect | SMT2200RM12UC

Physical	
Shipping Width	600MM, 60.0CM
Shipping Depth	980MM, 98.0CM
Units per Pallet	8.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	215.0BTU/hr

Conformance	
Approvals	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs