

Technical Specifications

APC Smart-UPS 3000VA LCD 230V with SmartConnect | SMT3000IC



APC Smart-UPS 3000VA LCD 230V with SmartConnect

SMT3000IC

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: USB cable

Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(1) IEC 320 C19 (Battery Backup) (2) IEC Jumpers (Battery Backup) (8) IEC 320 C13 (Battery Backup)
Transfer Time	6ms typical : 10ms maximum


Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20, Schuko CEE 7 / EU1-16P, British BS1363A
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V
Number of Power Cords	1
Other Input Voltages	220, 240

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS 3000VA LCD 230V with SmartConnect | SMT3000IC

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	RBC55 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	271Watts
Extendable Run Time	1
Battery Volt-Amp-Hour Capacity	816
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management

Interface Port(s)	SmartSlot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	365Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	435MM, 43.5CM
Maximum Width	197MM, 19.7CM
Maximum Depth	544MM, 54.4CM
Net Weight	52.5KG
Shipping weight	63.7KG
Shipping Height	699MM, 69.9CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS 3000VA LCD 230V with SmartConnect | SMT3000IC

Physical

Shipping Width	381MM, 38.1CM
Shipping Depth	762MM, 76.2CM
Color	Black
Units per Pallet	9.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	53.0dBA
Online thermal dissipation	375.0BTU/hr

Conformance

Approvals	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery, optional on-site warranties available, optional extended warranties available

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.