## **TP-Link Deco X20**

# AX1800 Whole Home Mesh Wi-Fi 6 System

## WIRELESS

Wi-Fi 6
IEEE 802.11ax/ac/n/a 5 GHz
IEEE 802.11ax/n/b/g 2.4 GHz
AX1800
5 GHz: 1201 Mbps (802.11ax)
2.4 GHz: 574 Mbps (802.11ax)
1-3 Bedroom Houses (1-pack)
3-4 Bedroom Houses (2-pack)
4-6 Bedroom Houses (3-pack)
TP-Link Mesh Technology
Optional Ethernet backhaul work together to link Deco units to
provide seamless coverage
2× Antennas (Internal)
Multiple antennas form a signal-boosting array to cover more
directions and large areas
Beamforming
Concentrates wireless signal strength towards clients to expand
WiFi range
High
Dual-Band
Distribute devices to different bands for optimal performance
MU-MIMO
Simultaneously communicates with multiple MU-MIMO clients
Cimataneously communicates with mattiple we will be circles
OFDMA
Simultaneously communicates with multiple WiFi 6 clients
4 Streams
More than enough bandwidth for connected devices

## WIRELESS

WIRELESS	
Working Modes	Router Mode Access Point Mode
HARDWARE	
Ethernet Ports	2× Gigabit Ports  *Per Deco Unit Supports WAN/LAN auto-sensing
Buttons	Reset Button
SECURITY	
WiFi Encryption	WPA-Personal WPA3-Personal
Network Security	SPI Firewall Access Control  HomeShield Security  Real-Time IoT Protection Malicious Site Blocker Intrusion Prevention System DDoS Attack Prevention Home Network Scanner
Guest Network	1× 5 GHz Guest Network 1× 2.4 GHz Guest Network
SOFTWARE	
Protocols	IPv4 IPv6
Service Kits	HomeShield
Parental Controls	HomeShield Parental Controls  Custom Profiles Professional Content Filter Library Family Time Bedtime Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports
WAN Types	Dynamic IP Static IP

## **SOFTWARE**

SOFTWARE	
	PPPoE PPTP L2TP
Quality of Service	HomeShield QoS  QoS by Device
Cloud Service	OTA Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link
Management	Deco App
TEST DATA	
WiFi Transmission Power	CE: <20 dBm (2.4 GHz) <23 dBm (5 GHz) FCC: <30 dBm (2.4 GHz) <30 dBm (5 GHz)
PHYSICAL	
Dimensions (W×D×H)	4.33 × 4.33 × 4.49 in (110 × 110 × 114 mm)
Package Contents	Deco X20 (3-pack) 3 Deco X20 Units 1 RJ45 Ethernet Cable 3 Power Adapters 1 Quick Installation Guide  Deco X20 (2-pack) 2 Deco X20 Units 1 RJ45 Ethernet Cable 2 Power Adapters 1 Quick Installation Guide
	Deco X20 (1-pack)

#### **PHYSICAL**

THIOIONE	
	1 Deco X20 Unit
	1 RJ45 Ethernet Cable
	1 Power Adapter
	1 Quick Installation Guide
OTHERS	
	Android 5.0 or later
	iOS 9.0 or later
System Requirements	*Note: The minimum system requirements will be updated
	alongside updates to the app, subject to official website
	information.
Certifications	CE, FCC, IC, RoHS, JPA, JRF, VCCI
	Operating Temperature: 0°C~40°C (32°F ~104°F)
	Storage Temperature: -40°C~60°C (-40°F ~140°F)
Environment	Operating Humidity: 10%~90% non-condensing
	operating manners, to be seen than contactioning

Storage Humidity: 5%~90% non-condensing